恒研光电 HENGYAN PHOTONICS

Single-Mode 3-Port Optical Circulator
(1064nm)

Specifications

Contact Hengyan Photonics with your custom specification needs.

Parameter		Unit	Value
Wavelength		nm	1064
Transmitting Direction		-	1→2, 2→3
Isolation (2→1, or 3→2) (23℃) (All SOP)	Typ.	dB	30
	Min	dB	25
Insertion Loss (1→2, or 2→3) (23℃) (All SOP)	Typ.	dB	1.8
	Max	dB	2.2
PDL	Max	dB	0.2
Return Loss	Min	dB	45
Directivity (1→3)	Min	dB	40
Optical Power Handling	Max	mW	150
Package Dimension		mm	65x12x10
Operating Temperature		℃	10 to 50
Storage Temperature		℃	0 to 60

* The above specifications are for parts without connectors. Adding connectors can affect the IL, RL, & PDL.
* SOP=State Of Polarization

Ordering Information

Contact Hengyan Photonics with your custom configuration needs.

CIR	Port	Wavelength	Fiber Type	Cable Type	Fiber Length	Connector
CIR	3=3-Port	10=1064nm X=Others	HI=HI1060 X=Others	B=250um bare fiber L=900um loose tube H=3mm X=Others	10=1.0m 15=1.5m 20=2.0m 30=3.0m X=Others	NE=None FA=FC/APC FC=FC/PC SA=SC/APC SC=SC/PC ST=ST/PC LA=LC/APC LC=LC/PC X=Others

Package Dimensions



No. 6, Mingda West Road, Laishan District, Yantai, Shandong, China
Tel: 18005354092 Email: tina.xing@hyphotonics.cn URL: https://www.hyphotonics.cn